

COPPER TUBE ASTM B-280

REFRIGERATION TUBES PER ASTM B 280, IN COILS, SOFT TEMPER

ENDS CAPPED, IN SHRINK WRAPPED BAG IN CARDBOARD BOX

	Outside Diameter (inch) (mm)	Thickness (inch)	Thickness (mm)	Nominal Weight, kgs (15 Metres)	Nominal Weight, kgs (15.24 Metres)
3/16	4.76	0.030	0.76	1.28	1.30
1/4	6.35	0.030	0.76	1.78	1.81
5/16	7.94	0.032	0.81	2.43	2.46
3/8	9.52	0.032	0.81	2.97	3.01
1/2	12.70	0.032	0.81	4.04	4.11
5/8	15.87	0.035	0.89	5.60	5.69
3/4	19.05	0.035	0.89	6.79	6.90
7/8	22.23	0.045	1.14	9.99	10.15



REFRIGERATION TUBES PER ASTM B280, STRAIGHT LENGTHS, HARD TEMPER

ENDS CAPPED, WOODEN BOX PACKING

Outside Diameter (inch)	Outside Diameter (mm)	Wall thickness (inch)	Wall thickness (mm)	Nominal Weight, kgs (5.8 Metres)	Nominal Weight, kgs (6 Metres)
3/8	9.52	0.030	0.76	1.08	1.12
1/2	12.70	0.035	0.89	1.71	1.77
5/8	15.88	0.040	1.02	2.46	2.55
3/4	19.05	0.042	1.07	3.12	3.23
7/8	22.23	0.045	1.14	3.90	4.04
1 ^{1/8}	28.58	0.050	1.27	5.63	5.83
1 ^{1/4}	34.93	0.055	1.40	7.62	7.89
1 ^{3/8}	41.28	0.060	1.52	9.81	10.15
2 ^{1/8}	53.98	0.070	1.78	15.09	15.61
2 ^{1/4}	66.68	0.080	2.03	21.31	22.05
3 ^{1/8}	79.38	0.090	2.29	28.67	29.66
3 ^{1/2}	92.08	0.100	2.54	36.93	38.21
4 ^{1/8}	104.78	0.110	2.79	46.21	47.8

Imperial Standard Wire Gauges (SWG)

SWG NO.	Inch	mm	SWG NO.	Inch	mm	SWG NO.	Inch	mm
16	0.064	1.63	19	0.040	1.02	22	0.028	0.71
17	0.056	1.42	20	0.036	0.91	23	0.024	0.61
18	0.048	1.22	21	0.032	0.81	24	0.022	0.56
25	0.02	0.51	27	0.016	0.41			

